

TLI-1550A



AA Size Rechargeable Lithium Ion Battery

Notice: The application load profile has to be approved by Tadiran.
Charging circuits and protections have to be designed in line with Tadiran guidelines.



Physical Characteristics

Length	51.5 mm. max
Diameter	14.7 ± 0.3 mm.
Weight	20 gr. max

Electrical Characteristics (for batteries stored at RT for 1 year or less)

Charge

Maximum Charge Voltage	4.1 V
Charge Method	CCCV (Constant Current/Constant Voltage)
Maximum Charge Current @ -20 to +50 °C	100 mA
Maximum Charge Current @ -40 to +85 °C	50 mA

For higher charging currents please consult Tadiran.

Discharge

Maximum Discharge Current @ 20 °C	
Continuous to 2.0 V (without PTC)	5 A
1 second pulse to 2.0 V	10 A
Charge / Discharge operating temperature	-40 to +85 °C
Storage Temperature Range	-55 to +85 °C
Cell impedance	< 100 mΩ at 1 kHz

Performance

Item	Value	Conditions
Maximum Capacity when charged to 4.1 V	330 mAh	Discharge at 100 mA to 2.0 V at 20 °C
	310 mAh	Discharge at 1000 mA to 2.0 V at 20 °C
	285 mAh	Discharge at 250 mA to 2.0 V at -20 °C
Charge / Discharge Cycles	5000	Charge 100 mA to 4.1 V EoC 20 mA, Discharge at 250 mA to 2.5 V at 20 °C
Capacity Retention after 100 cycles (reversible)	310 mAh	Discharge at 250 mA at 20 °C
Capacity Retention after 5 years at RT (reversible)	285 mAh	Discharge at 250 mA at 20 °C

Physical Cell / Battery Protection (to be applied by the user)

Item	Specification
Overcharge protection	Cell voltage should not be higher than 4.3 V
Overdischarge protection	Cell voltage should not be lower than 2.0 V

Battery pack assembly and usage considerations

- For 2 cells or more in series, voltage shall be monitored on each cell.
- For more than 2 cells in parallel, maximum charge current shall be limited to 250 mA for the whole pack.

Safety Considerations

The cells successfully passed the following tests:

Altitude simulation
Shock & Vibration
Short Circuit at RT, +57 and +85 °C
Heating at 130 °C
Forced Discharge
Crush and Impact
Temperature Cycling
Overcharge

UN Manual of Tests & Criteria

UL 1642, File MH12193

IEC 62133



Key Features

- ▣ Hermetically sealed (glass-to-metal)
- ▣ Wide operating temperature range
- ▣ Low self-discharge
- ▣ High output current
- ▣ High homogeneity
- ▣ End of life indication capability
- ▣ High reliability
- ▣ Lightweight
- ▣ Safe design
- ▣ Assembled in custom packs (per request)

Main Applications

- ▣ Emergency & Medical Devices
- ▣ Telemetry
- ▣ Navigation systems
- ▣ BUB in Metering
- ▣ Electronical Grid Monitoring
- ▣ Wireless sensors
- ▣ Energy Harvesting
- ▣ Automotive
- ▣ Asset, Container & Cargo Tracking
- ▣ Internet of things (IoT)

Ordering P/N:

TLI-1550A/S	61-1551-14100
TLI-1550A/T	61-1551-16200
TLI-1550A/TP	61-1551-16370
TLI-1550A/Z2/T *	61-1551-14200
TLI-1550A/Z2/TP *	61-1551-14350

* Z2 indicates that the cell is equipped with PTC SRP 200

WARNING:


Fire, Explosion, And Severe Burn hazards.
Do Not Crush, Disassemble, Heat Above 100°C, Short Circuit, Incinerate Or Expose Contents to water.

www.tadiranbatteries.com


THE INFORMATION PROVIDED HERE IS NECESSARILY OF A GENERAL NATURE. SINCE SPECIFIC PERFORMANCE DEPENDS ON ACTUAL OPERATING AND STORAGE CONDITIONS, OUR ENGINEERS WILL PROVIDE PARTICULAR APPLICATION INSTRUCTIONS UPON REQUEST. DATA SUBJECT TO REVISION WITHOUT NOTICE. ANY REPRESENTATION IN THIS BROCHURE CONCERNING PERFORMANCE ARE FOR INFORMATION PURPOSES ONLY AND NOT WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF FUTURE PERFORMANCE. TADIRAN'S STANDARD LIMITED WARRANTY, STATED IN ITS SALES CONTRACT OR ORDER CONFIRMATION FORM IS THE ONLY WARRANTY OFFERED BY TADIRAN.

Performance Data


Discharge curves at Room Temperature




Voltage Curves at 750 mA




Discharge curves at 2 A



Voltage Curves at 1200 mA



Charge / Discharge Cycling Performance



THE INFORMATION PROVIDED HERE IS NECESSARILY OF A GENERAL NATURE. SINCE SPECIFIC PERFORMANCE DEPENDS ON ACTUAL OPERATING AND STORAGE CONDITIONS, OUR ENGINEERS WILL PROVIDE PARTICULAR APPLICATION INSTRUCTIONS UPON REQUEST. DATA SUBJECT TO REVISION WITHOUT NOTICE. ANY REPRESENTATION IN THIS BROCHURE CONCERNING PERFORMANCE ARE FOR INFORMATION PURPOSES ONLY AND NOT WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF FUTURE PERFORMANCE. TADIRAN'S STANDARD LIMITED WARRANTY, STATED IN ITS SALES CONTRACT OR ORDER CONFIRMATION FORM IS THE ONLY WARRANTY OFFERED BY TADIRAN.