

## AA Size High Power Primary Li Metal Oxide Cell - Military Grade

*Notice: The application load profile has to be approved by Tadiran.*



### Physical Characteristics

Length	51 mm. max
Diameter	15.1 mm. max
Weight	20 gr. max

### Electrical Characteristics (for batteries stored at RT for 1 year or less)

Open Circuit Voltage	3.95 to 4.07 V
Closed Circuit Voltage at 0.1 sec on 0.5A load	3.88 V minimum

#### Discharge

Capacity under 20 mA at RT to 2.8 V	470 mAh
Capacity under 500 mA at RT to 2.8 V	425 mAh

#### Maximum Discharge Current

Continuous to 2.5 V	4.3 A
1 second pulse to 2.0 V	15 A

#### Discharge temperature range

Storage temperature range	-55 to +85 °C
Cell impedance at RT	Less than 100 mΩ at 1 kHz

### Accumulated Capacity Loss\*

Storage Time (years)	Storage Temperature			
	22 °C	55 °C	72 °C	85 °C
1	3 %	6 %	10 %	N/A
5	7 %	22 %	40 %	N/A
10	11 %	32 %	N/A	N/A
15	15 %	42 %	N/A	N/A
20	18 %	N/A	N/A	N/A

\* When tested at RT at 20 mA to 2.8 V

### Environmental

### Compliance with military specifications

Vibration	MIL-STD 810G	Method 514.6
Shock	MIL-STD 810G	Method 516.6
Temperature Shock	MIL-STD 810G	Method 503.5
Salt fog	MIL-STD 810G	Method 509.5
Altitude	MIL-STD 810G	Method 500.5
Acceleration*	50,000 g <sub>n</sub> (theoretical), 20,000 g <sub>n</sub> (tested) (dependent on duration)	
Spinning*	30,000 rpm (dependent on duration)	

\* These specifications are subject to testing and confirmation based on application requirements.

### Safety Considerations

The cells successfully passed the following tests:

Short circuit at RT & +57 °C	UN, IEC
Heating at 130 °C	UL, IEC
Forced Discharge	UL, UN, IEC
Crush	UL, IEC
Vibration	UN, IEC
Mechanical shock	UN, IEC

Standards referenced: UN Manual of Tests and Criteria Section 38.3, UL 1642, IEC 60086-4

### Key Features

- High Power 4.0 V
- Hermetically sealed (glass-to-metal)
- Wide operating temperature range
- Low self discharge
- Long storage life
- High g<sub>n</sub> survivability
- High homogeneity
- End of life indication capability
- High reliability
- Lightweight
- Safe design
- Assembled in custom packs (per request)

### Main Applications

- Ordnance fuzing power source
- Navigation systems
- Missile systems
- Telemetry
- Emergency systems
- Electronic warfare systems

### Ordering P/N

TLM-1550M/S	72-1456-22000
TLM-1550M/T	72-1456-22150
TLM-1550M/Z2/T *	72-1456-22200

\* Z2 indicates that the cell is equipped with PTC SRP 200

#### WARNING:


Fire, Explosion, And Severe Burn Hazard.  
Do Not Recharge, Crush, Disassemble,  
Heat Above 100°C, Short Circuit,  
Incinerate or Expose Contents to water.

[www.tadiranbatteries.com](http://www.tadiranbatteries.com)


THE INFORMATION PROVIDED HERE IS NECESSARILY OF A GENERAL NATURE. SINCE SPECIFIC PERFORMANCE DEPENDS ON ACTUAL OPERATING AND STORAGE CONDITIONS, OUR ENGINEERS WILL PROVIDE PARTICULAR APPLICATION INSTRUCTIONS UPON REQUEST. DATA SUBJECT TO REVISION WITHOUT NOTICE. ANY REPRESENTATION IN THIS BROCHURE CONCERNING PERFORMANCE ARE FOR INFORMATION PURPOSES ONLY AND NOT WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF FUTURE PERFORMANCE. TADIRAN'S STANDARD LIMITED WARRANTY, STATED IN ITS SALES CONTRACT OR ORDER CONFIRMATION FORM IS THE ONLY WARRANTY OFFERED BY TADIRAN.

## Performance Data


Discharge curves at Room Temperature




Pulse capability at Room Temperature




Discharge curves at 1 A




Pulse capability at 1 A



Capacity vs. OCV



Pulse capability at 0.5 A



THE INFORMATION PROVIDED HERE IS NECESSARILY OF A GENERAL NATURE, SINCE SPECIFIC PERFORMANCE DEPENDS ON ACTUAL OPERATING AND STORAGE CONDITIONS. OUR ENGINEERS WILL PROVIDE PARTICULAR APPLICATION INSTRUCTIONS UPON REQUEST. DATA SUBJECT TO REVISION WITHOUT NOTICE. ANY REPRESENTATION IN THIS BROCHURE CONCERNING PERFORMANCE ARE FOR INFORMATION PURPOSES ONLY AND NOT WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF FUTURE PERFORMANCE. TADIRAN'S STANDARD LIMITED WARRANTY, STATED IN ITS SALES CONTRACT OR ORDER CONFIRMATION FORM IS THE ONLY WARRANTY OFFERED BY TADIRAN.